



SFT1510 HDMI STREAMER

NMS IP: 192.168.1.30
User Name: user
Password: user

1. INTRODUCTION

The SFT1510 is housed with 3 HD input cards and can encode 12 HD signals with video compression standards of H.264 and H.265. It also comes with different IP protocols, making it ideal for any scenario that requires encoding and distributing multiple HD video signals.

2. FEATURES

1. Video encoding in H.264/H.265 and audio encoding in AAC.
2. Supports all major resolutions from 480i through 1080p60
3. Offers 12 IP output address in SPTS
4. IP streams over protocols of RTP/UDP/RTMP/RTSP/HTTP/HLS/SRT
5. Text overlay and image overlay in any place of TV screen
5. Easy configuration with built-in Web UI

3. SPECIFICATION

HDMI INPUT

Input Connector	HDMI 1.4 *12
-----------------	--------------

VIDEO

Encoding	H.264/H.265
----------	-------------

Input Resolution	1920*1080_60P/_50P
	1920*1080_60i/_50i
	1280*720_60P/_50P

Bit Rate	20 ~ 19000 Kbps
----------	-----------------

AUDIO

Encoding	AAC
----------	-----

IP OUTPUT

Output Connector	1*1000Mbps port
------------------	-----------------

Transport Protocol	RTP/UDP/RTMP/HTTP/HLS/SRT
--------------------	---------------------------

Output Transport Stream	SPTS
-------------------------	------

Broadcasting Mode	Unicast and Multicast
-------------------	-----------------------

Graphic Overlay	User-defined running text and image overlay
-----------------	---------------------------------------------

GENERAL

Input Voltage	90 ~264VAC, DC 12V 5A
---------------	-----------------------

Power Consumption	
-------------------	--

Rack Space	1RU
------------	-----

Dimension (WxHxD)	480*44*350mm
-------------------	--------------

Net Weight	4.11KG
------------	--------

Language	中文/ English
----------	-------------